

ABC powder



LICENCE No. KM532461



Dry Powder Fire Extinguishers are excellent multi-purpose fire extinguishers offering protection against class A, B, C fires and safe to use on electrical fires. These Kitemarked models are ideal for a wide range of domestic, industrial and commercial applications. Ideal for use to combat fires in vehicles, caravans, boats, agricultural machinery, farms, garages, in the home and offices.

- BS EN3 Kitemarked
- CE Marked
- Stored pressure
- Supplied with powder coated metal transport bracket
- Brass valve with easy to read pressure gauge
- Controlled discharge

Technical Specifications	FX1000DP	FX2000DP
Capacity	1kg	2kg
Extinguishing medium	Dry powder	Dry powder
Fire Rating	8A - 34B - C	13A - 55B - C
Pressurising gas & pressure	Nitrogen 14 Bar @ 20°C	Nitrogen 14 Bar @ 20°C
Discharge time	Under 8 seconds	Under 12 seconds
Operating temperature	-30°C to +60°C	-30°C to +60°C
Cylinder material	Steel	Steel
Cylinder weight & volume	0.7 kg - 1.4 litre	1.2 kg - 2.6 litre
Extinguisher height & cylinder diameter	335mm - 80mm	408mm - 108mm
Gross weight	2.1kg	3.4kg
Test pressure	29 Bar	29 Bar
Carton size (cm) & weight	11.5 x 11.5 x 35 - 2.2 kg	14 x 14 x 41 - 3.7 kg