

BC powder



LICENCE No. KM588149



Dry Powder Fire Extinguishers are small but highly efficient fire extinguishers offering protection against class B & C fires and safe to use on electrical fires. These models are ideal for a wide range of domestic applications and motor vehicles. Safe for use on live electrical equipment.

- Manufactured to BS6165:2019+A1:2022
- Fully Certified by BSI & Kitemarked
- Minimal maintenance required
- Factory sealed stored pressure
- Supplied with Durable plastic. Polypropylene bracket
- Aluminium light weight product
- Controlled discharge
- 5-Year manufacturer warranty / expiration. If any extinguisher becomes defective within the warranty period due to manufacturing faults and workmanship, at our discretion upon inspection, we will repair or replace. This warranty does not cover defects caused by environmental conditions, damage, misuse or neglect.

Technical Specifications	FX600DP / ALPHA600	FX900DP / BETA950
Capacity	600g	900g (FX900DP) / 950g (BETA950)
Extinguishing medium	BC Dry powder	BC Dry powder
Fire Rating	13 B - C	21 B - C
Pressurising gas & pressure	Nitrogen 8 Bar @ 20°C	Nitrogen 8 Bar @ 20°C
Discharge time	Under 6 seconds	Under 10 seconds
Operating temperature	-20°C to +60°C	-20°C to +60°C
Cylinder material	Aluminium	Aluminium
Cylinder weight & volume	66g - 0.6 litre	82g - 0.8 litre
Extinguisher height & cylinder diameter	268mm - 59mm	291mm - 66mm
Gross weight	720g	1020g / 1070g
Charge pressure	8 / 10 Bar	8 / 10 Bar
Single pack size (cm) & weight	30 x 8 x 8 - 820g	30 x 8 x 8 - 1100g
Multipack size (cm) & weight	32.5 x 29.5 x 14.5 - 7.5 kg (10/ pack)	32.5 x 29.5 x 14.5 - 8.5 kg (10/ pack)