

BC powder



LICENCE No. KM588149



Dry Powder Fire Extinguishers are small but highly efficient fire extinguishers offering protection against class B & C fires and safe to use on electrical fires. These models are ideal for a wide range of domestic applications and motor vehicles. Safe for use on live electrical equipment.

- Manufactured to BS6165:2002
- Fully Certified by BSI & Kitemarked
- Minimal maintenance required
- Factory sealed stored pressure
- Supplied with Durable plastic. Polypropylene bracket (FX600DP)
- Supplied with coated metal spring clip (FX900DP)
- Aluminium light weight product
- Controlled discharge
- 5 Year manufacturer warranty

Technical Specifications	FX600DP	FX900DP
Capacity	600g	900g
Extinguishing medium	BC Dry powder	BC Dry powder
Fire Rating	21 B - C	34 B - C
Pressurising gas & pressure	Nitrogen 7 Bar @ 20°C	Nitrogen 7 Bar @ 20°C
Discharge time	Under 6 seconds	Under 10 seconds
Operating temperature	-20°C to +60°C	-20°C to +60°C
Cylinder material	Aluminium	Aluminium
Cylinder weight & volume	66g - 0.6 litre	82g - 0.8 litre
Extinguisher height & cylinder diameter	268mm - 59mm	291mm - 66mm
Gross weight	720g	1020g
Test pressure	18 Bar	18 Bar
Single pack size (cm) & weight	30 x 8 x 8 - 820g	30 x 8 x 8 - 1100g
Multipack size (cm) & weight	32.5 x 29.5 x 14.5 - 7.5 kg (10/ pack)	32.5 x 29.5 x 14.5 - 8.5 kg (8/ pack)