



Multifoam extinguishers provide a fast and powerful means of tackling Class A solid fires (wood, paper, fibres), Class B flammable liquids (Petrol, solvents) and Class F deep fat cooking & burning oil fires, by forming a flame smothering seal over the surface and preventing re-ignition. This Aqueous Film Forming Foam solution is a water-based, highly effective fire-fighting medium particularly when used against fat and oil fires. This Multifoam fire extinguisher is ideal for multi-risk usage on small domestic fires around the home and various locations such as cars, taxis, caravans and boats.

Mains electrical power must be switched off before use on mains electrical fires, although this product has been safety tested to 1000V if used in error on live electrical fires.

- Tested and certified to BS6165 by MPA Dresden
- Professional grade AFFF fire fighting foam
- Easy to operate
- Aluminium light weight product
- Highly effective on oil fires, wood or textile fires & petrol fires
- Thermoplastic internal coating to prevent corrosion
- Controlled discharge
- Factory sealed stored pressure & ready for use
- Minimal maintenance required
- Contains no CFC
- Environment friendly product
- 3 year manufacturer warranty

Technical Specifications	FX600MF
Capacity	600ml
Extinguishing medium	Multifoam
Fire rating	5A-21B-5F
Pressurising gas & pressure	Nitrogen 10 Bar @ 20°C
Discharge time	30 seconds
Operating temperature	+5°C to +60°C
Cylinder material	Aluminum
Extinguisher height & cylinder diameter	291mm - 66mm
Cylinder weight and volume	82g - 0.8 litre
Gross weight	720g (or 755g with bracket)
Test pressure	18 Bar
Multipack size (cm) & weight	35 x 29 x 14.5 7.5 kg (10 units / pack) - with bracket 8/box @ 6.35Kg
Pallet size (cm) & Weight	120 x 100 x 132 - 680 kg (88 Cartons maximum / pallet) - w/b= 704pc / 560kg