

# FX1000AF Foam



Spray foam extinguishers provide a fast and powerful means of tackling class 'A' and 'B' type fires (flammable solids & liquids), by forming a flame smothering seal over the surface and preventing re-ignition. Aqueous Film Forming Foam or AFFF is a water-based, highly effective fire-fighting medium particularly when used against petrol and volatile liquids fires. This 1 Litre Foam model complies with the PSV Regulations Road traffic Act amendment 1995 (to the former BS5423 :1987) and can therefore be used on Public Service Vehicles such as taxis, mini buses and buses. Also ideal for small boats, caravans, workshop and around the home.

- CE Marked
- Spray nozzle passed the conductivity test at 35Kv
- Strong built. Steel cylinder with corrosion resistant finish & brass valve assemblies
- Thermoplastic internal coating to prevent corrosion
- Controllable squeeze grip operation
- Stored pressure & ready for use
- Easy to read pressure gauge
- Easy to recharge
- Supplied with powder coated metal transport bracket

Technical Specifications	FX1000AF
Capacity	1 litre
Extinguishing medium	AFFF Foam
Fire Rating	5A - 21B
Pressurising gas & pressure	Nitrogen 12 Bar @ 20°C
Discharge time	Under 10 seconds
Operating temperature	+ 5°C to +60°C
Cylinder material	Steel
Cylinder volume	1.25 litre
Extinguisher height & cylinder diameter	390mm - 110mm
Gross weight	2.3kg
Test pressure	27 Bar
Carton size (cm) & weight	13 x 9 x 35 - 2.4 kg
Multipack size (cm) & weight	37 x 37 x 28 - 19.2 kg (8 units/ pack)